

BIOQUELL L-4

A VERSATILE AND MOBILE SYSTEM FOR THE DECONTAMINATION OF ENCLOSURES AND ROOMS

Eliminate microbial contamination from your equipment or small enclosure systems, open spaces or rooms, and more using the multipurpose Bioquell L-4. Validated cycles can be achieved through quick and direct connections, simple room setup, or custom engineering solutions.

Our Hydrogen Peroxide Vapour technology effectively decontaminates isolators, BSCs, freeze dryers, pass-throughs, rack washers and more when connected to the Bioquell L-4.

Room decontamination options further showcase the system's versatility. Use the Bioquell L-4 inside a room by attaching a distribution head, or outside of a zone with connection solutions to meet your needs.



LEADING EFFICACY ACCEPTED GLOBALLY



Bioquell's Hydrogen Peroxide Vapour decontamination solutions, such as the Bioquell L-4, allow for a 6-log kill (99.9999% elimination) of bioburden from every exposed surface, protecting every step of your process or research. Whether passing through materials, working in an isolator, or freeze drying biological material, life science leaders trust the Bioquell L-4 to remove multiple risk sources of contamination.

ADAPTED TO MEET YOUR NEEDS



The flexibility of the Bioquell L-4 comes from its unique design. This system simply connects supply and return hoses to equipment via camlocks, or can be configured, to decontaminate a room with the addition of a vapour distribution head. For advanced needs, customised engineering requests can be accommodated as well. These may include the use of automation in a process or the installation of fixed pathways to introduce vapour in to a room.

QUICK SETUP, RAPID DECONTAMINATION



Unlike other decontamination options, with Bioquell there is no need to wait for a limited temperature or humidity range to be reached. Once started, the Bioquell L-4's dual loop technology takes effect by first emitting vapour, and then rapidly converting the hydrogen peroxide vapour into water vapour and oxygen. The details of every cycle are printed and real time cycle data is available over Ethernet (Modbus protocol) for recording on LIMS, BMS, SCADA or other data acquisition system.

YOUR BIOQUELL L-4 SYSTEM CAN BE OPTIMISED WITH:

- Room distribution and aeration accessories
- Comprehensive validation and documentation (IQ/OQ/GCD/PQ)
- Integration testing for BMS and more complex systems
- Cycle recording (thermal printer and solutions for real time cycle data)
- Remote start stop integration and automation
- Storage for up to 300 pre-programmed cycles

APPLICATIONS:

The Bioquell L-4's versatility provides bioburden elimination from numerous areas to protect you from a contamination event.

- Incubators
- Enclosed systems and equipment Isolators
- Pass-throughs
- Cage and rack washers
- Cleanroom and lab spaces up to 250m³
- Freeze dryers
- Material airlocks
- Bio-safety cabinets
- HEPA/Filter banks

MULTIPLE CONFIGURATIONS FOR INDIVIDUAL

For Equipment and Enclosures



Decontaminate equipment such as isolators, lyophilizers, BSCs and more with this standard capability

For Rooms and Open Spaces



Add a distribution head or work with Bioquell engineering for a custom solution to remove bioburden from areas up to 350m³*

Advanced Aeration Needs



Remove Hydrogen Peroxide Vapour faster, enhancing room turnaround time with up to two aeration units

*Subject to configuration, loading and environmental conditions

GET TECHNICAL WITH THE BIOQUELL L-4

Physical and safety data	Operating data	Power data
Dimensions and weight 550 x 1160 x 695 mm (21.7 x 45.6 x 27.4in) 76.5 kg (168.6 lbs)	Temperature limit at start of cycles: 15-30°C (59-86°F) Storage and opening: 0-35°C (32-95°F)	Regional power data requirements: 230v: single phase 50/60 Hz 6A 120v: single phase 50/60 Hz 12A 100v: single phase 50/60 Hz 15A
Locking brake (2x) Castor lock	Relative humidity (RH) limits at start of cycle: 10 to 80% max ² Storage and opening: 80% (max non-condensing)	Operational consumption: 1.44 kW/h (max) Supply: Installation category II
Vapour hoses and connectors 1.5 inch nominal bore 1.5 inch male/female camlock coupling	Hydrogen peroxide liquid 35% w/w Bioquell supply only ³ Standard model fits 500 ml and 1000 ml bottle 5 litre model only fits 5000 ml bottle	

¹ The Bioquell L-4 will allow a cycle to start up to a maximum of 35°C (95°F) starting temperature. However when operating above 30°C, please contact Bioquell to ensure the correct cycle is set up.

² If requiring to operate outside this range, refer to Bioquell or its agents.

³ For a full hydrogen peroxide specification, please contact Bioquell or its agents.

UK Headquarters

Bioquell UK Ltd
 E: enquiries@bioquell.com
 W: www.bioquell.com
 T: +44 (0)1264 835 835

Global

The Americas
 Bioquell Inc
 T: +1 215 682 0225

France
 Bioquell SAS
 T: +33 (0)1 43 78 15 94

Germany
 Bioquell GmbH
 T: +49 (0) 221 168 996 74

Ireland
 Bioquell Ireland
 T: +353 (0)61 603 622

China
 Bioquell Shenzhen Technology Company Ltd
 T: +86 755 8635 2622

Singapore
 Bioquell Asia Pacific Pte Ltd
 T: +65 6592 5145

