

thermo scientific



Intelligent microvolume analysis Pipette. Measure. Know.

NanoDrop One Microvolume UV-Vis Spectrophotometers



Proceed with confidence

Trusted by scientists worldwide, Thermo Scientific[™] NanoDrop[™] Microvolume UV-Vis Spectrophotometers fundamentally changed the way scientists evaluate nucleic acid and protein samples. With a patented sample-retention system* that enables direct measurements of 1 µL samples without dilution, and pre-programmed methods designed specifically for life scientists, NanoDrop Spectrophotometers have become indispensable in every laboratory.

> One Spectrophotometers are pushing the boundaries once again with the Thermo Scientific[™] Acclaro[™] Sample Intelligence technology that helps you understand the quality of your sample before you use it in downstream applications, bringing you one step closer to success.


Our next generation Thermo Scientific[™] NanoDrop[™]



Measure.



Know.





Accelerate discovery

Ensure experiment success with NanoDrop One technology

New features for today's scientists

- Stand-alone instrument with on-board control and high-definition touchscreen user interface
- Direct measurements from 1 to 2 µL of sample with auto-range pathlength technology
- Embedded applications for DNA, RNA, and protein quantification, full spectral data and purity ratios (260/280, 260/230)
- Sophisticated software identifies impurities in samples, can differentiate DNA from RNA, and delivers true analyte concentrations
- Advanced connectivity with easy data transfer to PC or network via Wi-Fi, USB, or Ethernet
- Expanded dynamic range—measure up to 27,500 ng/µL dsDNA or 400 mg/mL IgG with no dilution
- Fast and easy operation with ergonomic screen design and Auto-Measure capability
- Comply with US FDA 21 CFR Part 11 regulation with Thermo Scientific[™] Security Suite Software

NanoDrop One^c for experimental flexibility

The Thermo Scientific[™] NanoDrop One^c Spectrophotometer offers both a microvolume pedestal and a cuvette position.

Use cuvettes to:

- Measure dilute samples
- Perform kinetics experiments
- Measure optical density of bacterial cultures

For your convenience:


- Includes temperature control and stirring
- Cuvette position can be used with the instrument arm up or down

NANODROP ONE

Thermo

Streamline DNA and RNA workflows

The NanoDrop One application-based software guides you through each step of your DNA and RNA measurements with instant feedback, so you can proceed with confidence to your next experiment.



Know your sample

Powerful analysis with Acclaro Sample Intelligence technology

Accurate evaluation of RNA and DNA is critical to the success of downstream experiments, and it requires knowing both the concentration and purity of a sample. The presence of impurities in samples can result in inconclusive results, lengthy troubleshooting and costly delays.


Acclaro Sample Intelligence technology provides you with information about your sample in three different ways:

Acclaro Contaminant Identification


...uses sophisticated mathematical algorithms to identify contaminants in samples (for example phenol, guanidine salts and protein in nucleic acids), quantify the contaminant contribution to the total sample absorbance and calculate the true analyte concentration.

This dsDNA sample is flagged by Acclaro software; it has:

- Identified phenol as the contaminant
- Calculated the contribution of phenol to the total A260
- Calculated the "true" dsDNA concentration in the sample (corrected)



dsDNA sample contaminated with phenol. The absorbance contribution from the phenol (orange) is subtracted from the original result (blue) to obtain the corrected dsDNA concentration (green).



Evaluate protein samples effectively


Unlike nucleic acids which exhibit relatively consistent absorbance characteristics, each protein absorbs light differently based on its amino acid composition. Use the NanoDrop One Spectrophotometer to quantify your protein samples accurately and reproducibly. With simple workflows, an intuitive Protein Editor and applications to suit all needs, the NanoDrop One Spectrophotometer guides you to high-quality results.

Multiple protein applications

- Protein A280 for the quantification of purified protein samples
- **Protein A205** for the quantification of peptides and proteins that lack tryptophan and tyrosine residues
- Protein Colorimetric Protein Assays: select from a menu of pre-programmed assays (Bradford, BCA, Lowry and Thermo Scientific[™] Pierce[™] 660 nm) or create a custom method
- Verify protein labeling efficiency with the **Proteins and Labels** application that determines the carrier protein and the fluorescent dye concentrations.
- The Acclaro Contaminant Identification technology informs how much nucleic acid may be contaminating your protein sample, delivers true protein concentration



Tap to select an application from the Proteins home screen.



BCA assay results: total protein concentration (three red squares) and standard curve.

Assays	Direct A205*	Direct A280	Colorimetric Assays
Sample Type	Purified peptides and proteins that lack amino acids absorbing at 280 nm (e.g., tryptophan and tyrosine)	Purified proteins that contain aromatic amino acids	Any protein sample including uncharacterized protein mixtures and cell lysates.
Buffer Compatibility	Not suitable for buffers with strong UV absorbance (e.g., RIPA)	Not suitable for buffers with strong UV absorbance (e.g., RIPA)	Some assays are sensitive to detergents, reducing agents and other buffer properties (refer to manufacturers guidelines).
Other	Monitors the absorbance of the peptide bond	Need to know MW and extinction coefficient or E1% to calculate concentration	Protein-to-protein variation. Upper and lower detection limits vary between methods.
Preparation Time	None	None	Requires standard curves. Protein standards and samples need to be incubated with reagent solutions. Incubation time varies between assay methods.

* Scopes RK., (1974) Measurement of protein by spectrophotometry at 205 nm. Anal. Biochem. 59 (1):277-82.

Explore the capabilities

Improve your laboratory's productivity and expand your collaborations with connected laboratory instruments that accelerate your research. The NanoDrop One Microvolume UV-Vis Spectrophotometer comes equipped with features that help you connect, export, print and view data, so you can move one step closer to discovery.

Advanced connectivity

The NanoDrop One Spectrophotometer brings enhanced connectivity to the center of your workflow.

- Choices for exporting data—transfer results with a USB, Wi-Fi or Ethernet connection to your PC or connect to the Thermo Fisher Connect cloud-based platform to securely upload and store your data
- View, organize and share data on a PC—view and organize experiments using the NanoDrop One PC Viewer software
- Printer options-print results directly from the instrument via Ethernet, Wi-Fi, or USB
- 24/7 access to data—view and share data anytime, anywhere from any device when you store data on the Thermo Fisher Cloud using the free NanoDrop Cloud App

Connect via WiFi or Ethernet



- Networked or shared drives
 PC
- Printers



 Dymo[®] and external printers



- PC (NanoDrop One PC Viewer Software)
- Shared drives
- USB
- Thermo Fisher Connect NanoDrop Cloud App

View data



- Modern browsers
- Mac[®] & PC
- Mobile iOS, Android[™] & Windows[®] devices

When you need more

- Use the UV-Vis application to monitor multiple wavelengths simultaneously
- Create new custom methods to analyze your special samples
- Download custom methods from our website to quantify gold nanoparticles, chlorophyll, glucose, hemoglobin and more
- Monitor bacterial growth on the pedestal or with a cuvette using the OD600 application
- Run time-based kinetic experiments on the NanoDrop One^c Spectrophotometer





OD600

Custom Methods



Kinetics

thermo scientific



Technical specifications

Instrument Control		Built-in touchscreen
Minimum Sample Volume		1 μL
Limit of Detection	dsDNA (RNA)	Pedestal: 2.0 (1.6) ng/µL Cuvette: 0.2 (0.16) ng/µL
	BSA (lgG)	Pedestal: 0.06 (0.03) mg/mL Cuvette: 0.006 (0.003) mg/mL
Maximum Concentration	dsDNA (RNA)	Pedestal: 27,500 (22,000) ng/µL
	BSA (IgG)	Pedestal: 820 (400) mg/mL
Measurement and Data Proc	essing Time	8 seconds
Measurement Repeatability ¹		Typical: 0.002 A (1.0 mm path) or 1%CV, whichever is greater
Wavelength	Range	190–850 nm
	Accuracy	±1 nm
Photometric	Range (10 mm equivalent)	Pedestal: 0–550 A Cuvette: 0–1.5 A
	Accuracy ²	3% at 0.97 A, 302 nm
Resolution (Spectral Bandwid	dth)	≤1.8 nm (FWHM at Hg 254 nm)
Pathlength		0.030 to 1.0 mm auto-ranging
Light Source		Xenon flash lamp
Detector		2048-element CMOS linear image sensor
Dimensions (W \times D \times H)		20 × 25.4 × 32.3 cm (8 × 10 × 12.7 in.
Weight		3.6 kg (7.9 lbs.)
Operating Voltage		12 V (DC)
Power Consumption		Operating: 12–18 W Standby: 5 W
Stirring (cuvette only)		9 speeds
Temperature Control (cuvette	e only)	37 °C

On-Board Control	Operating System	Android™	
	CPU	Quad Core ARM [®] Cortex [™] -A9 Processor	
	Display	7-inch, 1280 \times 800 high-definition color display	
	Touchscreen	Multipoint capacitive touch	
	Gesture Recognition	Single point, single point hold, swipe and pinch	
	Glove Compatibility	Compatible with lab gloves	
	Internal Storage	32 GB flash memory	
	Audio	Built-in speaker	
Connectivity	Three USB-A ports, Ethernet, Bluetooth $^{\otimes}$ and Wi-Fi 3		
PC Software Requirements	Windows® 7 and 10, 64 bit		
Accessory Support	DYMO LabelWriter 450 printer, Bluetooth keyboard, mouse and barcode reader		
Applications Support	Nucleic Acid A260, A260/A280, A260/A230 and Labeled Nucleic Acids; Protein A280 and A205, Protein Pierce 660, Protein Bradford, Protein BCA, Protein Lowry, Labeled Proteins, OD600, Kinetics, UV-Vis, and Custom Methods		
Language Support	Chinese French Germa	an Japanese Korean Polish Spanish English	

Ordering information

Instruments	Part Number
NanoDrop One spectrophotometer (Pedestal position only)	ND-ONE-W ⁴
NanoDrop One ^c spectrophotometer (Pedestal and cuvette positions)	ND-ONEC-W ⁴
Accessories and Consumables	
NanoDrop One Productivity kit	ND-PP1
NanoDrop One ^c Productivity kit	ND-PP1C
Dymo LabelWriter 450 printer with labels	PNTR-LW400
PR-1 Reconditioning Compound kit	CHEM-PR1-KIT
PV-1 Performance Verification solution	CHEM-PV-1

⁴ Wi-Fi model not available in all countries. Please contact your NanoDrop distributor to confirm the correct part number in your region.

Choose the NanoDrop instrument that's right for your lab needs.

 $^1\,\text{SD}$ of 10 individual measurements at 0.97 A $^2\,\text{Absorbance}$ expressed at Abs/mm at 25 °C

³Only available on instruments with Wi-Fi/Bluetooth support



NanoDrop One/One^c Fast, accurate analysis of DNA, RNA, protein

Learn more at thermofisher.com/nanodropone



Thermo Scientific[™] NanoDrop[™] Lite Routine A260 and A280 measurements



Thermo Scientific[™] NanoDrop[™] 8000 Measure up to 8 samples at a time



Thermo Scientific[™] NanoDrop[™] 3300 Fluorescence analysis without filters from 1 µL



© 2018-2021 Thermo Fisher Scientific Inc. All rights reserved. All NanoDrop instruments are approved to CE and UL/CSA. Android is a trademark of Google LLC. ARM is a registered trademark and Cortex-A9 is a trademark of ARM Limited. Bluetooth is a registered trademark of Bluetooth SIG, Inc. DYMO is a registered trademark of Esselte Corporation. LabelWriter is a registered trademark of DYMO Corporation. Windows is a registered trademarks of Microsoft Corporation. Mac is a registered trademark of Apple Inc. All other trademarks are the property of Thermo Fisher Scientific and its subsidiaries. Not all products are available in all countries. **BR52720_E 01/21M**