

ROTOR BEATER MILL SR 300



The Rotor Beater Mill SR 300 is suitable for **coarse and fine size reduction, either in batches or continuously**. It can process **dry, soft, medium-hard, organic and inorganic substances**.

With its **adjustable speed** of 3,000 to 10,000 rpm the rotor beater mill SR 300 is intended for **universal use**: from sample preparation in laboratories up to preparing sample batches in pilot plants or production facilities. The grinding chamber, the feed hopper and the material inlet are completely made from **high quality stainless steel**.

APPLICATION EXAMPLES

bentonite, chemical products, coal, coke, drugs, feed pellets, fertilizers, food, graphite, gypsum, herbs, pharmaceutical materials, plant materials, plastics, powder coating, resins, rice, salts, seeds, soils, spices, sugar, ...

PRODUCT ADVANTAGES

- | suitable for batchwise operation of larger quantities
- | high final fineness
- | adjustable speed for different applications
- | easy cleaning thanks to exchangeable push-fit grinding insert, rotor and cassette
- | grinding chamber, feed hopper and material inlet and outlet of stainless steel
- | optional grinding inserts 180° for grinding of hard-brittle materials by additional impact
- | optional distance rotor to reduce frictional heat
- | removable hopper for easy cleaning
- | electric engine brake
- | defined final fineness due to bottom sieves with aperture sizes from 0.08 - 10 mm
- | central locking device
- | wide range of accessories including various collection and feeding systems, rotors and sieves

FEATURES


Applications	size reduction, deagglomeration
Field of application	agriculture, chemistry / plastics, construction materials, environment / recycling, food, geology / metallurgy, medicine / pharmaceuticals
Feed material	soft, medium-hard
Material feed size*	< 25 mm
Final fineness*	< 50 µm
Speed at 50 Hz (60 Hz)	3,000 - 10,000 min ⁻¹ (in steps of 500 min ⁻¹)
Rotor peripheral speed	22 .. 72 m/s
Types of rotors	standard / distance
Material of grinding tools	rotor and sieves of stainless steel
Sieve sizes	trapezoid holes 0.08 / 0.12 / 0.20 / 0.25 / 0.35 / 0.50 / 0.75 / 1.00 / 1.25 / 1.50 / 2.00 mm round holes 3.00 / 4.00 / 10.00 mm
Hinged hopper	removeable hopper
Dust extraction unit	optional cyclone
Collector capacity	5 l / optional: 30 l
Drive	3-phase motor
Electrical supply data	200 .. 240 V
Power connection	1-phase
Engine brake	yes, electric
Protection code	IP 41
Power consumption	2.5 kW
W x H x D closed	600 x 1200 x 700 mm (with base frame)
Net weight	~ 60 kg (with base frame)
Standards	CE

*depending on feed material and instrument configuration/settings

FUNCTIONAL PRINCIPLE

Size reduction and deagglomeration in the SR 300 are achieved by **impact and shear effects**. The feed material passes from the hopper into the center of the grinding chamber where it is crushed between the rotor, sieve and grinding inserts.

As soon as the material is smaller than the aperture size of the sieve it enters the collecting receptacle. The quick-acting door lock ensures easy access to the grinding chamber for quick cleaning. With their safety switch, splashback and access barrier in the inlet and outlet areas, Rotor Beater Mills offer the highest degree of operating safety.



[Click to view video](#)

www.retsch.com/sr300